

Dragger™ Assembly Instructions
Model: S-2 Tail-Dragger Dragger®

Assembly Note: All reference to “right” and “left” orientation is made while standing behind the tug and looking forward.

Remove all items from shipping container and spread out neatly. Contents include lower frame, upper frame (handle), 2 wheels, 2 cotter pins (in zip lock bag in center of wheel).

Step 1: Assemble handle using the bolts provided in the lower frame. Handle can be mounted on top of or below the lower frame, depending on users ergonomic preference. Insert bolts from the top. Hand grips can be up or down again depending on user ergonomic preference.

Step 2: Adjustment Pins/Bolts: There is one (1) bolt and one pin in the lower frame. Only one bolt/pin is required for most uses. However, you may use a second bolt/pin for RV or similar aircraft that have a smaller tail wheel.

Step 3: Remove the small plastic bag of parts from the inside of the wheel. Mount the tug wheels to the frame with the flush side of the wheel to the outside of the frame. Install each cotter pin through the hole at each end of the axle and bend to hold in place.

Refer to <http://dragger.com/tail-dragger-draggers> for additional information on loading the aircraft onto the S-2 Tail-Dragger Dragger.

Airtug, LLC is not responsible for aircraft damage sustained when proper clearance is not maintained by the operator between the tug and the aircraft, and surroundings.

